**B** Tubing

# 594TJ – TOUGHJACKET<sup>™</sup> SAE 100R19 Hydraulic Hose

Copolyester Core Tube - 4,000 psi

Four-spiral wire performance in a two-wire braid construction.

#### Features

- · Four-spiral wire hose performance in a high tensile two-wire braid construction
- Excellent flexibility
- Consistent long-lengths
- TOUGHJACKET Polyurethane cover for best abrasion resistance

#### Construction

- Tube: Copolyester
- Reinforcement: One or two high tensile steel wire braids
- Cover: TOUGHJACKET Polyurethane™

#### **Operating Parameters**

- Temperature Range:
  - Petroleum based hydraulic fluids and lubricating oils within a temperature range -40°F (-40°C) to 212°F (100°Č)
  - Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to 185°F (85°C); \*\*594TJ-10 is limited to 135°F (57°C)

Nominal I.D.

mm

6.3

10

12.5

16

19

inch

1/4

3/8

1/2

5/8

3/4

Maximum

0.D.

mm

12.5

16.3

21.5

26.4

29.7

inch

0.49

0.64

0.85

1.04

1.17

- Water/glycol hydraulic fluids limited to 135°F (57°C)
- Vacuum Rating: 28 inch Hg
- Change in length at Max. Working Pressure:
  - -4 to -10: +/- 2% -12. +2% to -4%
- Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)



594TJ-4

594TJ-6

594TJ-8\*

594TJ-12\*

594TJ-10\* \*\*

Part

Number

NU
Parker Parlier Touchiesen: 5940

#### Compliance

- Meets/Exceeds SAE 100R19 performance
- MSHA compliant cover

#### **Fittings**

- 56 Series pg. E-33 43 Series Fittings available from Parker Hose Products Division
- For most Parker products, Crimp Die Selection charts are found online at www.parker.com/crimpsource
- Access instructions are on pg. G-3

#### Notes

- Non-perforated cover
- \*Two wire braid

### Color

🔸 🔴 🔴 🔴

Minimum

Bend

Radius

mm

44.5

63.5

88.9

100.0

120.0

inch

1-3/4

2-1/2

3-1/2

4

4-3/4



Visit the webpage

Permanent

Fitting Series

56

56

43

43

43

Weight

lbs./ft.

0.13

0.19

0.39

0.59

0.72

kg/mtr

0.19

0.28

0.59

0.88

1.07

## WARNING

This product can expose you to chemicals including Antimony Oxide (Antimony Trioxide), which is known to the State of California to cause cancer, and 2-Imidazolidinethione, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Maximum

Working

Pressure

MPa

28.0

28.0

28.0

28.0

28.0

psi

4,061

4,061

4,061

4,061

4,061



Coiled Air Hose & Fittings

D

Fittings

E